

HOME STANDBY GENERATOR SYSTEMS

Battery Information

Battery Information

Battery Specifications	33 Amp Hour (Vertical)	50 Amp Hour (Horizontal)	55 Amp Hour (Liquid Cooled)
Volts	12 Volt DC	12 Volt DC	12 Volt DC
Amps (min) CCA = Cold Cranking Amps	350 CCA	600 CCA	650 CCA
Battery Type	AGM (Absorbed Glass Mat)	AGM (Absorbed Glass Mat)	VRLA (Valve Regulated Lead Acid)
Terminal Hardware	M8	M6	N/A, battery must have top posts
Dimensions (Max):			
Width	5.325 in (135 mm)	5.5 in (140 mm)	7.5 in (191 mm)
Length	7.875 in (200 mm)	9.0 in (230 mm)	11.25 in (286 mm)
Height	6.875 in (175 mm)	8.25 in (210 mm)	10.0 in (254 mm) including posts
Recommended Battery Suppliers and Battery Item Numbers			
Batteries Plus – Werker Brand	WKA12-33C*	WKA12-55C/FR	WKDC12-80P
Storage Battery Systems (SBS)	S-12330	MH19767	
Vision		MH25860	

Note: Do NOT use an automotive type battery. All batteries must be a valve regulated lead acid type.

* Requires two (2) installer-supplied M6 flat washers